



## Features

- Compact & Rugged Design
- DC Output ON/OFF
- Voltage & Current Output Preset Facility for Safety
- Constant Voltage / Constant Current Mode
- 3 Digit DPM V and A
- High Stability & Close Regulation  $\pm 0.01\% \pm 3\text{mV}$
- Low Ripple  $< 1\text{mV rms}$
- Overload Protection

## Technical Specifications

<b>Constant Voltage Mode</b>	Output Range	0 - 32V.
	Regulation	Line $\leq 0.01\% \pm 3\text{mV}$ for 10% change in line. Load $\leq 0.01\% \pm 3\text{mV}$ for load change from zero to full load.
	Ripple & Noise	$< 1\text{mV rms max.}$
	Indication	CV mode LED Green.
<b>Constant Current Mode</b>	Output Range	0 - 2A.
	Regulation	Line $\leq 0.01\% \pm 2\text{mA}$ for 10% change in line. Load $\leq 0.1\% \pm 4\text{mA}$ for load change in output voltage from zero to max. output voltage.
	Ripple & Noise	$\leq 2\text{mA rms max.}$
	Indication	CC mode LED Red.
<b>Protections</b>	Automatic overload and short circuit protection.	
<b>Metering</b>	Digital Standard	Single meter to read V/A of output with a selector switch.
<b>Input Line Voltage</b>	230V AC $\pm 10\%$ , 50Hz.	
<b>Dimensions</b>	95 (W) x 285 (D) x 177 (H) mm.	
<b>Weight</b>	4.14 Kgs.	

WE PURSUE A POLICY OF CONTINUOUS DEVELOPMENT AND PRODUCT IMPROVEMENT. THUS THE SPECIFICATIONS IN THIS DOCUMENTS AND THE LOCATION OF CONTROLS ON THE FRONT PANEL MAY BE CHANGED WITHOUT NOTICE.

Jan 2022